GuangDong FuDianKang Power Co., Ltd.
ShenZhen FuDianKang Diesel Gensets Co., Ltd.
Tel: 86-13710087995
Web: www.fdkenergy.com Email: info@fdkenergy.com

DATA SHEET

DIESEL GENERATOR 2000KW
MODEL#FDK-M2500/H1
50HZ/1500RPM
MITSUBISHI MODEL: S16R2-PTAW-C

General Features:

- All qualified generator sets are subjected to a comprehensive performance test which includes 50% load, 70% load, 100% load, 110% load and to check, verify that all control systems, alarm and shut-down protection.
- Equipped with battery charger and 24V high performance maintenance-free lead-acid starting batteries and connecting cables.
- Stainless galvanized zinc plates with strong corrosion-proof.
- Vibration isolators between the engine/alternator and base frame.
- Equipped with industrial silencer and flexible exhaust hose.
- Designed to comply with ISO8528/GB2820.
- Powered by Mitsubishi engine and coupled with Stamford alternator.
- Water jacket preheater, oil heater and double air cleaner, etc. are available.

FDK Diesel Generator Set Data

Genset Model	FDK-M2500/H1	Engine Make	SME
Prime Power	1800KW/2250KVA	Engine Model	S16R2-PTAW-C
Standby Power	2000KW/2500KVA	Alternator model	Stamford S7L1D-H41
Output Frequency / Rated speed	50Hz/1500rpm	Control System	DSE7320
Rated Voltage	230V/400V	Phase	Three

(1) **Prime power**: The rating is available for an unlimited of annual operating hours in variable load applications, in accordance with ISO8528-1.A 10% overload is available for a period of 1 hour within 12-hour period of operation, in accordance with ISO 3046-1.

(2) **Standby power**: The rating is applicable for supplying emergency power in variable load applications for up to 200 hours per year in accordance with ISO8528-1. Overload is not allowed.

(3) **Rated voltage**: available with customer requirement.

Engine Specifications (DETAILED in APPENDIX)

Engine Model	S16R2-PTAW-C	Bore x Stroke (mm x mm)	170×220
Engine Manufacturer	SME Shanghai	Displacement	79.9L
Cylinder quantity	16	Compression Ratio	14.0:1
Cylinder Arrangement	V type	Prime power / Speed (KW/RPM)	1960/1500
Cycle	Four strokes	Standby power/ Speed (KW/RPM)	2167/1500
Aspiration	Turbo charged	Speed governor	Electronic

Piston Speed	9m/s	Fuel Consumption at 100% load	464
Maximum Regenerative Power	152kw	Starter motor	24V
Total Lubrication System Capacity (L)	290	Alternator	24V
Coolant Capacity Engine Only (L)	157	Maximum Overspeed Capacity	2100RPM

Alternator Specifications

Alternator model	S7L1D-H41	Number of phases	3
Alternator manufacturer	STAMFORD	Rated voltage	400V (Available with custom requirements)
Exciter type	Single bearing, Brushless, Self-excited	Power factor	0.8
Rated output prime power	2250KVA	Voltage regulation NL-FL	≤±1%
Rated speed	1500 rpm	Insulation grade	H
Rated frequency	50Hz	Protection grade	IP23

Alternator option: Leroy Somer, MECC, Marathon, Engga, Faraday

Control System DSE7320 (DETAILED in INSTRUCTION)

DSE7320 is an advanced control module based on micro-processor, containing all necessary functions for protection of the genset and the breaker control. It can monitor the mains supply, breaker control and automatically start the engine when the mains are abnormal. Accurately measure various operational parameters and display all values and alarms information on the LCD. In addition, the control module can automatically shut down the engine and indicate the engine failure.

FEATURES

- Microprocessor control, with high stability and credibility.
- Monitoring and measuring operational parameters of the mains supply and genset.
- Indicating operation status, fault conditions, all parameters and alarms.
- Multiple protections; multiple parameters display, like pressure, temp. etc.
- Manual, automatic and remote work mode selectable.
- Real time clock for time and date display, overall runtime display, 250 log entries.
- Overall power output display.
- Integral speed/frequency detecting, telling status of start, rated operation, overspeed etc.
- Communication with PC via RS485 OR RS232 interface, using MODBUS protocol.

Soundproof Enclosure Specification

FDK silent generator is designed by professional acoustic engineers based on years of experience. Now we can make the noise of the generator less than 80-85dB(A) at 1m, or 70-75dB(A) at 7m, 60-65dB(A) at 15m.

FEATURES

- Multi-way air intake and exhaust guarantee the power performance of the generator.
- Large-scale impedance combined type silencer effectively reduces noise of the generator.
- Internal high performance rubber damper and flexible materials reduce vibration.
- Base mounted fuel tank supports the generator running for 8 hours.

Optional

GuangDong FuDianKang Power Co., Ltd.
ShenZhen FuDianKang Diesel Gensets Co., Ltd.
Tel: 86-13710087995
Web: www.fdkenergy.com Email: info@fdkenergy.com

Generator set	Alternator	Low environment Temp	ATS
☐ Open generator set	☐ Stamford	☐ Water heater	☐ CHINT
☐ Silent generator set	☐ Marathon	☐ Oil heater	☐ SCHNEIDER
☐ Trailer generator set	☐ Mecc Alte	☐ Battery heater	☐ ABB
☐ ABB MCCB circuit breaker	☐ Leroy Somer		
	☐ Farady		
	☐ Engga		
Fuel system	**Control system**	**Voltage**	**Synchronized system**
☐ 12hrs base tank	☐ AMF function	☐ 415/240V	☐ CHINT Cabinet
☐ 24hrs base tank	☐ ATS control cabinet	☐ 400/230V	☐ SCHNEIDER Cabinet
☐ Dual wall base fuel tank	☐ DSE7320	☐ 380/220V	☐ DSE8610 Module
☐ Outside fuel tank	☐ DSE7510	☐ 220/127V	☐ COMAQ Module
	☐ GU620A	☐ 200/115V	☐ DEIF Module

Dimension & Weight

Open

Overall Size: L×W×H (mm)	6500×2650×2879
Weight (kg)	17000

Soundproof Version

Overall Size: L×W×H (mm)	9000X3000X3400
Weight (kg)	24000

Sales Promises

- FDK provides a full line of brand new and high-quality products. Each and every unit is strictly factory tested before shipment.
- Quality warranty is according to our standard conditions: 12 months from BL date or 1000 running hours, whichever comes first.
- Service and parts are available from FDK or distributors in your location.
- FDK guarantee use **BRAND NEW & GENUINE MACHINE.**

FuDianKang