GuangDong FuDianKang Power Co., Ltd.
ShenZhenFuDianKang Diesel Gensets Co., Ltd.
Tel:86-13710087995
Web: www.fdkenergy.comEmail: info@fdkenergy.com

DATA SHEET

DIESEL GENERATOR 660KW
MODEL#FDK-W825/H1
50HZ/1500RPM
WEICHAI MODEL: 6M33D725E310

General Features:

- All qualified generator sets are subjected to a comprehensive performance test which includes 50% load, 70% load, 100% load, 110% load and to check, verify that all control systems, alarm and shut-down protection.
- Equipped with battery charger and 24V high performance maintenance-free lead-acid starting batteries and connecting cables.
- Stainless galvanized zinc plates with strong corrosion-proof.
- Vibration isolators between the engine/alternator and base frame.
- Equipped with industrial silencer and flexible exhaust hose.
- Designed to comply with ISO8528/GB2820.
- Powered by Cummins engine and coupled with Stamford alternator.
- Water jacket preheater, oil heater and double air cleaner, etc. are available.

FDK Diesel Generator Set Data

Genset Model	FDK-W825/H1	Engine Make	WEICHAI
Prime Power	600KW/750KVA	Engine Model	6M33D725E310
Standby Power	660KW825KVA	Alternator model	NIANFENG NF354H
Output Frequency / Rated speed	50Hz/1500rpm	Control System	HGM6110
Rated Voltage	230V/400V	Phase	Three

(1) **Prime power**: The rating is available for an unlimited of annual operating hours in variable load applications, in accordance with ISO8528-1.A 10% overload is available for a period of 1 hour within 12-hour period of operation, in accordance with ISO 3046-1.

(2) **Standby power**: The rating is applicable for supplying emergency power in variable load applications for up to 200 hours per year in accordance with ISO8528-1. Overload is not allowed.

(3) **Rated voltage**: available with customer requirement.

Engine Specifications (DETAILED in APPENDIX)

Engine Model	6M33D725E310	Bore x Stroke (mm x mm)	150×185
Engine Manufacturer	WEICHAI (China)	Displacement	19.6L
Cylinder quantity	6	Compression Ratio	15:1
Cylinder Arrangement	Vertical in-line	Prime power / Speed (KW/RPM)	675/1500
Cycle	Four stroke	Standby power/ Speed (KW/RPM)	725/1500
Aspiration	Turbo-charged	Speed governor	Electrical

ISO9001:2015FDK reserves the right to change the specifications and designs without notice.

Total Lubrication System Capacity (L)	61	Fuel Consumption at 100% load (g/KWh)	200.5 at 1500rpm
Coolant Capacity (L)	N.A.		

Alternator Specifications

Alternator model	NF354H	Number of phase	3
Alternator manufacturer	NIANFENG	Rated voltage	400V (Available with custom requirements)
Exciter type	Single bearing, Brushless, Self-excited	Power factor	0.8
Rated output prime power	750KVA	Voltage regulation NL-FL	≤±1%
Rated speed	1500 rpm	Insulation grade	H
Rated frequency	50Hz	Protection grade	IP23

Alternator option: Leroy Somer, MECC, Marathon, Engga, Faraday

Control System HGM6110 (DETAILED in INSTRUCTION)

HGM6110 is an advanced control module based on micro-processor, containing all necessary functions for protection of the genset and the breaker control. It can monitor the breaker control and automatically start the engine when the mains are abnormal. Accurately measure various operational parameters and display all values and alarms information on the LCD. In addition, the control module can automatically shut down the engine and indicate the engine failure.

FEATURES

- Microprocessor control, with high stability and credibility.
- Monitoring and measuring operational parameters of the mains supply and genset.
- Indicating operation status, fault conditions, all parameters and alarms.
- Multiple protections; multiple parameters display, like pressure, temp. etc.
- Manual, automatic and remote work mode selectable.
- Real time clock for time and date display, overall runtime display, 250 log entries.
- Overall power output display.
- Integral speed/frequency detecting, telling status of start, rated operation, overspeed etc.
- Communication with PC via RS485 OR RS232 interface, using MODBUS protocol.

Soundproof Enclosure Specification

FDK silent generator is designed by professional acoustic engineers based on years of experience. Now we can make the noise of the generator less than 80-85dB(A) at 1m, or 70-75dB(A) at 7m, 60-65dB(A) at 15m.

FEATURES

- Multi-way air intake and exhaust guarantee the power performance of the generator.
- Large-scale impedance combined type silencer effectively reduce noise of the generator.
- Internal high performance rubber damper and flexible materials reduce vibration.
- Base mounted fuel tank supports the generator running for 8 hours.

FuDianKang

Optional

Generator set	Alternator	Low environment Temp	ATS
☐ Open generator set	☐ Stamford	☐ Water heater	☐ CHINT
☐ Silent generator set	☐ Marathon	☐ Oil heater	☐ SCHNEIDER
☐ Trailer generator set	☐ Mecc Alte	☐ Battery heater	☐ ABB
☐ ABB MCCB circuit breaker	☐ Leroy Somer		
	☐ Farady		
	☐ Engga		
Fuel system	**Control system**	**Voltage**	**Synchronized system**
☐ 12hrs base tank	☐ AMF function	☐ 415/240V	☐ CHINT Cabinet
☐ 24hrs base tank	☐ ATS control cabinet	☐ 400/230V	☐ SCHNEIDER Cabinet
☐ Dual wall base fuel tank	☐ DSE7320	☐ 380/220V	☐ DSE8610 Module
☐ Outside fuel tank	☐ DSE7510	☐ 220/127V	☐ COMAQ Module
	☐ GU620A	☐ 200/115V	☐ DEIF Module

Dimension & Weight

Open

Overall Size: L×W×H (mm)	4000×1760×2173
Weight (kg)	5200

Soundproof Version

Overall Size: L×W×H (mm)	5800×2400×2800
Weight (kg)	7500

Sales Promises

- FDK provides a full line of brand new and high quality products. Each and every unit is strictly factory tested before shipment.
- Quality warranty is according to our standard conditions: 12 months from BL date or 1000 running hours, whichever comes first.
- Service and parts are available from FDK or distributors in your location.
- FDK guarantee use **BRAND NEW & GENUINE MACHINE.**

FuDianKang